



Filter Systems

DESIGNED AND MANUFACTURED IN THE UK

F1500, F2500, F3000, F6000, F9000, F12000, F19000, F24000, F30000

March May Filter Systems have been designed specifically for the surface finishing industry. Manufactured in the UK, these modular systems can be easily modified to match exact customer requirements.

With many years of experience, we offer technical advice especially with efficiency, safety and cost at the forefront.

FEATURES

Available in Polypropylene, CPVC or PVDF to handle the complete range of chemicals and temperatures.

Threaded sealing caps.

Knife-edge sealing location ring.

A wide range of Seal-less leak free magnetically coupled pumps.

IP55 protected motors with chemically resistant paint finish.

Air release vent.

Viton or EPDM O-ring seals.

Single, 3, 5, and 12 column chambers available.

Pressure gauge as standard on modules F6000 and above.



BENEFITS

Extremely reliable and robust.

Offer a positive seal on the cartridge for the lifetime of the system.

Simple and fast cartridge changing.

Designed to meet specific customer requirements.

March May specialises in the manufacture of bespoke pumps and filters by modifying units from our wide range of standard models and motor types.

Standard Specifications

SMALLER APPLICATIONS

Systems with flow rates from 1500 to 3000 lph available, combined with a single column.

Supplied complete with cartridges and 2m suction / discharge hoses.

F1500-10	1500 lph
F2500-20	2500 lph
F3000-30	3000 lph
Column sizes	1 x 10"-20"-30"
Voltages	230-1ph-50Hz 415-3ph-50Hz



INTERMEDIATE APPLICATIONS

Systems with flow rates from 3000 to 9000 lph available, combined with 5 column filter chambers.

Supplied complete with pressure gauge, cartridges and 2m suction / discharge hoses.

F3000-510	3000 lph
F6000-520	6000 lph
F9000-530	9000 lph
Column sizes	5 x 10"-20"-30"
Voltages	230-1ph-50Hz 415-3ph-50Hz



LARGER APPLICATIONS

Systems with flow rates from 12000 to 30000 lph are produced in conjunction with a range of column filter chambers.

Supplied complete with pressure gauge, cartridges and 2m suction / discharge hoses.

F12000-1210	12000 lph
F19000-1220	19000 lph
F24000-1230	24000 lph
F30000-1240	30000 lph
Column sizes	12 x 10"-20"-30"-40"
Voltages	415-3ph-50Hz

